

Specification Sheet

Part Number: T250L0X2



Heavy Duty Cable Tie, 34.7" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg

| | |
|--------------------------------|---|
| Article Number | 111-24601 |
| Type | T250L |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Heavy-duty design offers higher tensile strength.• Buckle feature on head allows excess strap to be tucked away after installation.• Bent tail ensures a quick and simple installation. |
| Quantity Per | bag |
| Product Description | HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description | Heavy Duty Cable Tie, 34.7" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg |

Global Part Name

T250L-PA66-BK

Minimum Tensile Strength (Imperial)

250.0

Minimum Tensile Strength (Metric)

1115.0

Length L (Imperial)

34.7

Length L (Metric)

880.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.49

Width W (Metric)

12.4

Bundle Diameter Min (Imperial)

0.47

Bundle Diameter Min (Metric)

12.0

Bundle Diameter Max (Imperial)

10.0

Bundle Diameter Max (Metric)

254.0

| | |
|--|--|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL ANSI/UL 1565 UL ANSI/UL 746B UL ANSI/UL 62275 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 25 |
| Package Quantity (Metric) | 25 |
| Customs Number | 3926909987 |
| Content Unit(BMEcat) | pcs. |
| Weight (Metric) | 15.5 |

