

THIS DRAWING IS A CONTROLLED DOCUMENT.


Part #	L (meters)	L (feet)	LC-Duplex Secure, Rose		LC-Duplex, Beige	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-1906056-1	0.950 - 1.050	3.11 - 3.44	0.5	-	0.5	-
0-1906056-2	1.950 - 2.050	6.39 - 6.72	0.5	-	0.5	-
0-1906056-3	2.950 - 3.050	9.67 - 10.00	0.5	-	0.5	-
0-1906056-4	3.920 - 4.080	12.86 - 13.38	0.51	-	0.51	-
0-1906056-5	4.920 - 5.080	16.14 - 16.66	0.51	-	0.51	-
0-1906056-6	5.920 - 6.080	19.42 - 19.94	0.51	-	0.51	-
0-1906056-7	6.920 - 7.080	22.70 - 23.22	0.51	-	0.51	-
0-1906056-8	7.920 - 8.080	25.98 - 26.50	0.51	-	0.51	-
0-1906056-9	8.850 - 9.150	29.03 - 30.01	0.51	-	0.51	-
1-1906056-0	9.850 - 10.150	32.31 - 33.30	0.52	-	0.52	-
1-1906056-1	10.850 - 11.150	35.59 - 36.58	0.52	-	0.52	-
1-1906056-2	11.850 - 12.150	38.87 - 39.86	0.52	-	0.52	-
1-1906056-3	12.850 - 13.150	42.15 - 43.14	0.52	-	0.52	-
1-1906056-4	13.850 - 14.150	45.43 - 46.42	0.52	-	0.52	-
1-1906056-5	14.850 - 15.150	48.72 - 49.70	0.52	-	0.52	-
1-1906056-6	15.840 - 16.160	51.96 - 53.01	0.52	-	0.52	-
1-1906056-7	16.830 - 17.170	55.21 - 56.33	0.53	-	0.53	-
1-1906056-8	17.820 - 18.180	58.46 - 59.64	0.53	-	0.53	-
1-1906056-9	18.810 - 19.190	61.71 - 62.95	0.53	-	0.53	-
2-1906056-0	19.800 - 20.200	64.96 - 66.27	0.53	-	0.53	-
2-1906056-1	20.790 - 21.210	68.20 - 69.58	0.53	-	0.53	-
2-1906056-2	21.780 - 22.220	71.45 - 72.90	0.53	-	0.53	-
2-1906056-3	22.770 - 23.230	74.70 - 76.21	0.53	-	0.53	-
2-1906056-4	23.760 - 24.240	77.95 - 79.52	0.54	-	0.54	-
2-1906056-5	24.750 - 25.250	81.20 - 82.84	0.54	-	0.54	-
2-1906056-6	25.740 - 26.260	84.44 - 86.15	0.54	-	0.54	-
2-1906056-7	26.730 - 27.270	87.69 - 89.46	0.54	-	0.54	-
2-1906056-8	27.720 - 28.280	90.94 - 92.78	0.54	-	0.54	-
2-1906056-9	28.710 - 29.290	94.19 - 96.09	0.54	-	0.54	-
3-1906056-0	29.700 - 30.300	97.44 - 99.40	0.55	-	0.55	-
3-1906056-1	30.690 - 31.310	100.68 - 102.72	0.55	-	0.55	-
3-1906056-2	31.680 - 32.320	103.93 - 106.03	0.55	-	0.55	-
3-1906056-3	32.670 - 33.330	107.18 - 109.35	0.55	-	0.55	-
3-1906056-4	33.660 - 34.340	110.43 - 112.66	0.55	-	0.55	-
3-1906056-5	34.650 - 35.350	113.68 - 115.97	0.55	-	0.55	-
3-1906056-6	35.640 - 36.360	116.92 - 119.29	0.55	-	0.55	-
3-1906056-7	36.630 - 37.370	120.17 - 122.60	0.56	-	0.56	-
3-1906056-8	37.620 - 38.380	123.42 - 125.91	0.56	-	0.56	-
3-1906056-9	38.610 - 39.390	126.67 - 129.23	0.56	-	0.56	-
4-1906056-0	39.600 - 40.400	129.92 - 132.54	0.56	-	0.56	-
4-1906056-1	40.590 - 41.410	133.16 - 135.85	0.56	-	0.56	-
4-1906056-2	41.580 - 42.420	136.41 - 139.17	0.56	-	0.56	-

Qty	U of M	Description	Item No.
2	piece	Trace Label	7
4	piece	Eyelet/Shrink tube assembly - White	6
AR	meter	2 fiber, 62.5/125, 2.0mm, Twinzip, Orange, OFNR (Riser)	5
2	piece	LC Connector Assy, 1.6mm-2.0mm, MM	4
2	piece	LC Connector Assy, MM	3
2	piece	LC Duplex clip, black	2
4	piece	LC, SC, FC Straight Boot, Beige	1

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHER PARTY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
 CE
 DIST
 16

Rev	Per	EC#	RELEASE	DATE	DN	APVD
A				0/26/2007	-	JD
P	LTR		REVISION RECORD			



DIMENSIONS:
 meters
 0 PLG ± -
 2 PLG ± -
 3 PLG ± -
 4 PLG ± -

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PLG ± -
 2 PLG ± -
 3 PLG ± -
 4 PLG ± -

Restricted To:

DIN	Cable Assy Configurator	MATERIAL		HEAT TREAT	
CHK	Jeremy Duncan				
APVD	Jeremy Duncan				
NAME	FO C/A - 2 fiber, 62.5/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex				
SCALE	NTS	SIZE	A2	DRAWING NO	C- 1906056
SHEET	2 of 4	REV	A		

Label 1

Per specification 107-1645-1



This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1




This label is used on all lengths on this drawing.

THIS DRAWING IS A CONTROLLED DOCUMENT. DWG NO

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS, INC. IT IS TO BE KEPT CONFIDENTIAL AND NOT DISCLOSED TO ANY OTHERS. ANY UNAUTHORIZED DISCLOSURE OR USE OF THIS INFORMATION IS STRICTLY PROHIBITED. TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC
CE
DIST
16

A	Rev Per EC#	RELEASE	D/26/2007	-	JD				
P	LTR	REVISION RECORD	DATE	DN	APVD				



DIMENSIONS: meters

0 PLC	±	-
2 PLC	±	-
3 PLC	±	-
4 PLC	±	-

TOLERANCES UNLESS OTHERWISE SPECIFIED:

Restricted To:

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Jeremy Duncan		
APVD	Jeremy Duncan	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, 62.5/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex		
SCALE	NTS	SIZE	A2
DRAWING NO	C- 1906056		SHEET
REV	4 of 4		A