

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C(NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C(NOTES 3)
	OPERATING HUMIDITY RANGE	20% TO 80%(NOTES 2)	STORAGE HUMIDITY RANGE	40% TO 70%(NOTES 2)(NOTES 3)
	VOLTAGE		APPLICABLE CONNECTOR	DF81※-30S-0.4H(##)
	CURRENT		APPLICABLE CABLE	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT NOTE2: NON CONDENSING NOTE3: THE TERM "STORAGE" REFERS TO PRODUCTS STORED FOR A LONG PERIOD PRIOR TO MOUNTING AND USE. THE OPERATING TEMPERATURE AND HUMIDITY RANGE COVERS THE NON-CONDUCTING CONDITION OF CONNECTORS AFTER BOARD MOUNTING AND THE TEMPORARY STORAGE CONDITIONS OF TRANSPORTATION, etc Unless otherwise specified, refer to JIS C 5402,IEC60512.		APPROVED	TS. SAKATA	12. 11. 12
		CHECKED	HS. OZAWA	12. 11. 12
		DESIGNED	TP. MATSUMOTO	12. 11. 09
		DRAWN	TP. MATSUMOTO	12. 11. 09

Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. ELC4-340821-01

HRS	SPECIFICATION SHEET	PART NO.	DF81-30P-LCH	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL662-8107-3-00	△ 1/1