



DUALBAND PHANTOM ELITE[®] ANTENNA IS IDEAL FOR CELLULAR AND PCS APPLICATIONS

Laird's unique patented Phantom Elite[®] dual-band cellular antenna operates simultaneously on Cellular 821-896 MHz and PCE 1850-1990 MHz and is a tough antenna for outdoor or indoor applications. Suitable for outdoor and indoor applications, the revolutionary design measures only 2.7" and features field diversity with both vertical and horizontal polarization. This gives the antenna diversity, frequency agility, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications.

The industry standard NMO mounting socket mates with all Laird's magnetic, trunk lid, and hole mounts. A threaded permanent stud mount model is also available for vandal resistant mounting on brackets, panels, ceilings or any other kind of housing.

FEATURES 


- True Field Diversity design ensures uninterrupted transmissions in urban canyons and rural drop off areas
- Phantom[®] outperforms a 3dB whip in many applications
- U.S. Patent Nos. 5,977,931 – 6,292,156 and 7,209,096

MARKETS


- Public safety
- Transportation
- Utility
- Military mobile
- Fixed radio applications

ANTENNA PATTERNS

**Vertical-to-Vertical Polarization
Azimuthal Pattern (Y, Z, or E-plane)**



Cellular: 821-896 MHz



PCS: 1850-1990 MHz

SPECIFICATIONS

ELECTRICAL	
Frequency Range	821-896 MHz 1850-1990 MHz
Frequency Bandwidth (low)	75 MHz@VSRW < 2:1
Frequency Bandwidth (high)	140 MHz@VSRW < 2:1
VSWR	< 2.1
Return Loss	-10dB max
Nominal Gain	3 dB-M.E.G.
Maximum Power	100 W
Nominal Impedance	Ω50
Polarization	Vertical & Horizontal
Pattern	Patented Field Diversity (Omni-directional)
Half-Power Beamwidth (Elevation° x Azimuth°)	130° x 360°
Cable & Mount	MB195 (Sold Separately)
Terminations	NMO or P Mount
Tuning:	Connector None

MECHANICAL	
Material	High Heat ABS
Operating Temperature	-40° C to 85° C

MODEL AND ORDERING INFORMATION

MODEL	DESCRIPTION	COLOR	RADOME HEIGHT	WEIGHT CONNECTOR
ETRA821/18503	Dual Band Phantom® Elite	Black	2.70"	.15 lbs NMO
ETRA821/18503P	Dual Band Phantom® Elite	Black	2.70"	.25 lbs N Female
ETRA821/18503	Dual Band Phantom® Elite	White	2.70"	.15 lbs NMO
ETRA821/18503P	Dual Band Phantom® Elite	White	2.70"	.25 lbs N Female

Addition of "P" to the model numbers indicates Permanent Mount.

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-PHANTOM ELITE DUAL-BAND 0215

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.