

SERIES: P78A-1000 | **DESCRIPTION:** DC-DC CONVERTER

FEATURES

- up to 1 A current output
- pin compatible with LM78XX linear regulators
- non-isolated switching regulator
- wide input voltage range
- efficiency up to 91%
- low ripple and noise
- short circuit protection
- ultra-compact SIP3 package
- low profile
- -40°C to +85°C temperature range




MODEL

| MODEL | input voltage | | output voltage | output current | output power | ripple & noise ¹ | efficiency ² |
|-------------|---------------|-------------|----------------|----------------|--------------|-----------------------------|-------------------------|
| | typ (Vdc) | range (Vdc) | (Vdc) | max (mA) | max (W) | max (mVp-p) | typ (%) |
| P78A03-1000 | 24 | 7~28 | 3.3 | 1000 | 3.3 | 120 | 87 |
| P78A05-1000 | 24 | 8~28 | 5 | 1000 | 5 | 120 | 91 |

Notes: 1. At full load, nominal input, 20 MHz bandwidth oscilloscope, output terminated with a 0.1 μF multilayer low ESR ceramic capacitor.
 2. At min Vin.
 3. All specifications measured at: Ta=25°C, nominal input voltage, rated output load, and after warm up unless otherwise specified.

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|-------------------------|------------------------|-----|-----|-----|-------|
| operating input voltage | 3.3 Vdc model | 7 | 24 | 28 | Vdc |
| | 5 Vdc model | 8 | 24 | 28 | Vdc |
| no load input current | Vin = 24 Vdc | | 1.5 | | mA |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|--------------------------------------|---|-----|-----|------|-------|
| maximum capacitive load ¹ | | | | 220 | μF |
| line regulation | measured from low to high line, full load | | | ±1 | % |
| load regulation | measured from 10~100% load, typical Vin | | | ±1.5 | % |
| voltage accuracy | | | ±3 | ±5 | % |
| switching frequency | Vin = 12 Vdc | | 330 | | kHz |

Note: 1. Maximum capacitive load is tested at nominal input voltage and full load.

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|---------------------------------|-----|-----|-----|-------|
| over current protection | output shut down, auto recovery | | | 200 | % |
| short circuit protection | output shut down, auto recovery | | | | |

SAFETY AND COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|-----------|--|-----------|-----|-----|-------|
| MTBF | as per MIL-HDBK-217F, full load, 25 °C | 3,875,000 | | | hours |
| RoHS | 2011/65/EU | | | | |

ENVIRONMENTAL


| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curve | -40 | | 85 | °C |
| storage temperature | | -55 | | 125 | °C |
| operating humidity | non-condensing | | | 95 | % |

SOLDERABILITY

| parameter | conditions/description | min | typ | max | units |
|----------------|-------------------------|-----|-----|-----|-------|
| wave soldering | see wave solder profile | | | 260 | °C |

Note: 2. The wave solder profile is measured on lead temperature.
3. Need to keep the solder parts internal temperature less than about 210°C.

Lead-free Recommended Soldering Profile








MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|------------------|--|-----|-----|-----|-------|
| dimensions | 11.6 x 8.5 x 10.4 | | | | mm |
| case material | non-conductive black plastic (UL94V-0) | | | | |
| potting material | epoxy (UL94V-0) | | | | |
| weight | | | 2 | | g |

MECHANICAL DRAWING


units: mm
 tolerance: XX.X=±0.50 mm
 XX.XX=±0.25 mm

| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | +Vin |
| 2 | GND |
| 3 | +Vout |




Recommended PCB Layout
Top View

DERATING CURVE




EFFICIENCY CURVES

Efficiency vs. Load
3.3 Vdc output model



Efficiency vs. Load
5 Vdc output model



APPLICATION CIRCUIT

Figure 1




Table 1

| Optional External Components | |
|------------------------------|-----------------|
| C1 | 10 μ F MLCC |
| C2 | 10 μ F MLCC |


- Notes:
1. To protect the converter during power-up, use soft start power supply.
 2. The converter cannot be used as a positive to negative converter.

PACKAGING

units: mm

Tube Size: 520 x 16.5 x 9.3 mm

QTY: 42 pcs



REVISION HISTORY

| rev. | description | date |
|------|-----------------|------------|
| 1.0 | initial release | 05/16/2016 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC[®]

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.