

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-40°C TO +85°C	STORAGE TEMPERATURE RANGE	-40°C TO +85°C
	POWER	2 W CW	CHARACTERISTIC IMPEDANCE	50 Ω ( DC TO 4.0 GHz)
	OPERATING RELATIVE HUMIDITY	95% MAX	USED CONNECTOR	BNC.P-J

### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

#### CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

#### ELECTRIC CHARACTERISTICS

V.S.W.R.	MUST BE UNDER THE STD.VALUE AT FREQUENCY DC TO 1.0 GHz	MAXIMUM OF 1.15	X	X
	MUST BE UNDER THE STD.VALUE AT FREQUENCY 1.0 TO 4.0 GHz	MAXIMUM OF 1.25		
ATTENUATION	MUST BE UNDER THE STD.VALUE AT FREQUENCY DC TO 2.0 GHz	5.7 TO 6.3 dB.	X	X
	MUST BE UNDER THE STD.VALUE AT FREQUENCY 2.0 TO 4.0 GHz	5.7 TO 6.5 dB		

#### MECHANICAL CHARACTERISTICS

VIBRATION	FREQUENCY 10 TO 2000 Hz, TOTAL AMPLITUDE 1.52 mm, 98 m/s <sup>2</sup> AT 4 HOURS FOR 3 DIRECTIONS.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X	-
SHOCK	ACCELERATION : 490 m/s <sup>2</sup> DURATION : 11 ms , HALF SINE WAVE 3 BOTH AXIAL DIRECTIONS, 3 TIMES EACH	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X	-

#### ENVIRONMENTAL CHARACTERISTICS

MOISTURE RESISTANCE	EXPOSE TO -10 TO 65 °C, 80 ~ 98 %, TOTAL 10 CYCLES(240 h). THEN LEAVE IT FOR ONE HOUR OR TWO IN THE AMBIENT TEMPERATURE AND HUMIDITY.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X	-
THERMAL SHOCK	TEMPERATURE-58~-55→20~35→85~88→20~35°C TIME 30 → 5 → 30 → 5 min TEST 5 CYCLES AND LEAVE IT FOR ONE HOUR OR TWO.	①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X	-
SALT ATMOSPHERE (CORROSION)	SALT SOLUTION CONCENTRATION 5% SALT WATER SPRAY FOR 48 HOURS.	NO CORROSION WHICH AFFECTS THE OPERATION OF COMPONENT.	X	-

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0				

REMARK ROHS COMPLIANT	APPROVED	MT. SHIBUTANI	12. 01. 27
	CHECKED	KY. SHIMIZU	12. 01. 27
	DESIGNED	TK. SAWAGUCHI	12. 01. 26
	DRAWN	TK. SAWAGUCHI	12. 01. 26

Unless otherwise specified, refer to MIL-STD-202.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-030150-01
--	-------------	----------------

<b>HRS</b>	SPECIFICATION SHEET	PART NO.	AT-506 (40)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL354-0038-0-40	1/1