



FIBER #	COLOR
1	DUMMY
2	ORANGE
3	GREEN
4	DUMMY

TRACE NUMBER{ TYCO ELECTRONICS XXXXXXXXXX  
 TYCO ELECTRONICS P/N{ 1938250-1

$\triangle 6$  LABEL DETAIL

- MAX INSERTION LOSS: 1.0 dB (1310nm)
- $\triangle 2$  PART SHIPPED WITH PIECE OF TAPE TO HOLD FIBER BUFFERS IN PLACE. TAPE TO BE REMOVED AFTER TERMINATING BUFFERED FIBER END OF ASSEMBLY.
- PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF TYCO ELECTRONICS STANDARD 230-702.

LIGHTRAY MPX CONNECTOR FIBER PATH

1.000±0.051 [39.37±2.00]	1938250-1
L METERS [INCHES]	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	J.W.DAVIS	02OCT07	Tyco Electronics Corporation Harrisburg, PA 17105-3608
DIMENSIONS: METERS [INCHES]		CHK	J.BARRY	02OCT07	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	J.BARRY	02OCT07	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		NAME	PIGTAIL, FIBER OPTIC, 2 FIBER SINGLEMODE BUFFERED FIBER, LIGHTRAY MPX W/PINS		
MATERIAL	FINISH	PRODUCT SPEC	APPLICATION SPEC		RESTRICTED TO
		WEIGHT	SIZE CAGE CODE DRAWING NO A2 00779 C-1938250		
CUSTOMER DRAWING			SCALE	NTS	SHEET 1 OF 1 REV A