



JKL PART NUMBER	LENGTH A +/- 1.5mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (Cd/m2)	*RATED LIFE (HRS)
BF20218-24B	218mm	RGB HIGH OUTPUT WHITE 8400°k x = .290 y = .305	1250 @ 0°C	500	5 ± 1	46,000 TYP.	40,000
BF20226-24B	226mm		1275 @ 0°C	510			
BF20292-24B	292mm		1650 @ 0°C	660			
BF20325-24B	325mm		1830 @ 0°C	735			

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
			TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP							
DRAWN BY L. WENGSTROM			APPVD BY DATE J.V. 8/25/10		SIZE A	FSCM NO. 55335	DRAWING NO. BF 20-24B			
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE		RELEASED DATE 8/14/03	REVISION DATE 8/25/10	REV. NO. B	SHEET 1 OF 1		
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE								
B	RATED LIFE HRS TO 40,000	8/25/10								
A	RATING ADDITIONS & CHANGES RELEASED TO CAD MULTI LIST	4/26/04 8/14/03								