

Apr.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

| APPLICABLE STANDARD | | | | |
|---------------------|-----------------------------|---|---------------------------|--|
| RATING | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C ⁽¹⁾ | STORAGE TEMPERATURE RANGE | -10 °C TO 60 °C ⁽²⁾ |
| | VOLTAGE | 100 V AC | STORAGE HUMIDITY RANGE | 40 % TO 70 % ⁽²⁾ |
| | CURRENT | 0.5 A (SIGNAL CONTACT) ⁽³⁾ 3 A (MF CONTACT) | OPERATING HUMIDITY RANGE | RELATIVE HUMIDITY 85% max (NOT DEWED) |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|--------------------------------------|---|--|----|----|
| CONSTRUCTION | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | x | x |
| MARKING | CONFIRMED VISUALLY. | | x | x |
| ELECTRIC CHARACTERISTICS | | | | |
| CONTACT RESISTANCE | 100 mA(DC OR 1000Hz) | SIGNAL CONTACT : 90 mΩ MAX. MF CONTACT : 30 mΩ MAX. | x | — |
| INSULATION RESISTANCE | 250 V DC. | 1000 MΩ MIN. | x | — |
| VOLTAGE PROOF | 300 V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | x | — |
| MECHANICAL CHARACTERISTICS | | | | |
| INSERTION AND WITHDRAWAL FORCES | MEASURED BY APPLICABLE CONNECTOR. | INSERTION FORCE: 40 N MAX. WITHDRAWAL FORCE: 4 N MIN. | x | — |
| MECHANICAL OPERATION | 500 TIMES INSERTIONS AND EXTRACTIONS. | ① CONTACT RESISTANCE: SIGNAL CONTACT : 100 mΩ MAX. MF CONTACT : 40 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — |
| VIBRATION | FREQUENCY 10 TO 55 TO 10Hz, APPROX 5min SINGLE AMPLITUDE : 0.75 mm, 10 CYCLES FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — |
| SHOCK | 490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — |
| ENVIRONMENTAL CHARACTERISTICS | | | | |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h. | ① CONTACT RESISTANCE: SIGNAL CONTACT : 100 mΩ MAX. MF CONTACT : 40 mΩ MAX. | x | — |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55 → +85 °C TIME 30 → 30 min. UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2~3 MIN) | ② INSULATION RESISTANCE :1000 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — |
| SULFUR DIOXIDE | EXPOSED AT 25±2°C, 75±5%RH, 25 PPM FOR 96 h. (TEST STANDARD: JIS C 60068) | NO HEAVY CORROSION. | x | — |
| RESISTANCE TO SOLDERING HEAT | 1)REFLOW SOLDERING : PEAK TMP : 260°C MAX REFLOW TMP: 220°C MIN FOR 60sec 2) SOLDERING IRONS : 360°C MAX. FOR 5 sec. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL. | x | — |
| SOLDERABILITY | SOLDERED AT SOLDER TEMPERATURE 240±3°C FOR IMMERSION DURATION, 3 sec. | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | x | — |

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---|--------------------------|-------------|-----------------|----------|
| △ | | | | |
| REMARKS ⁽¹⁾ INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING. ⁽²⁾ "STORAGE" MEANS A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE ASSEMBLY TO PCB. ⁽³⁾ THE RATED CURRENT APPLIES TO PER CONTACT. | | APPROVED | HS. OKAWA | 09.10.13 |
| | | CHECKED | KI. HIROKAWA | 09.10.13 |
| | | DESIGNED | TH. SANO | 09.10.13 |
| Unless otherwise specified, refer to JIS-C-5402. | | DRAWN | TH. SANO | 09.10.13 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | DRAWING NO. | ELC4-159075-00 | |
| HRS | | PART NO. | FX18-60P-0.8SH | |
| SPECIFICATION SHEET | | CODE NO. | CL579-0003-8-00 | △ 1/1 |
| HIROSE ELECTRIC CO., LTD. | | | | |