


Part Number: 5408UE



Security & Sound, #20-10c, BC, CMR

Product Description

Security & Sound Cable, Riser-CMR, 10-20 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Security Systems, Intercom/PA Systems, Sound/Audio Systems, Power Limited Controls, and Single Line Telephone.
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
20	7x28	BC - Bare Copper	10

Conductor Count:	10
Conductor Size:	20 AWG

Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.008 in

Color Chart

Number	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Gray

Outer Shield Material

Material
Unshielded

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.244 in	0.018 in	Yes

Construction and Dimensions

Cabling

Twists
3 twist/ft

Print Legend:	NEW GENERATION(R) BY BELDEN-M 5408UE CMR 75C 10C20 (UL) E108998 OR C(UL) CMG (2 FT., 7 DIGIT SEQUENTIAL) FEET
---------------	---

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR

10.2 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor

24.7 pF/ft

Shielding: Unshielded

Current

Max. Recommended Current [A]

2.6 Amps per conductor @ 25°C A

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating: 75°C

Operating Temp Range: -20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight: 49.9 lbs/1000ft

Max Recommended Pulling Tension: 126 lbs

Min Bend Radius/Minor Axis: 2.5 in

Standards

NEC Articles: 800

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-04-01

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flammability, LSOH, Toxicity Testing

C(UL) Flammability: FT4

UL Flammability: UL1666 Riser

UL voltage rating: 300 V RMS

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 6408UE

Part Number

Variants

Item #	Color	Footnote
5408UE 0081000	Gray	C

Footnote: C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.