



NOTES:

1. RoHS COMPLIANT
2. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0; BLACK
 - PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
 - PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
4. CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.)
5. SEALING COMPOUND: PUR; BLUE
6. CAPACITANCE: 180pF ± 20%
7. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
8. CONNECTOR IS PART MARKED: 241□26840X CONEC ABC (see note 4)

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance	dim. in mm	scale: 2:1 (5:1)		
							material: SEE NOTES	
				date	name	title: D-SUB FILTER MALE 9pos. SOLDER CUP		
				drawn 03.07.12	Henneboel			
				appd. 03.07.12	Fischer			
				norm				
				d-old		dwg no:		DIN-A3
	a	Original				24K1A1387		
rev.	description	date	name			part no: 241□26840X (see note 4)		sh: 1