



- ① INCLUDED WITH HEAD SUB ASS'Y, ITEM #14.
- ② WHEN REPLACING HEAD SUB ASS'Y, ITEM #14 OR CYLINDER, ITEM #3, ASSEMBLE HEAD SUB ASS'Y TIGHT TO CYLINDER. CENTER PUNCH THRU #5-40 HOLE. REMOVE CYLINDER & DRILL .125 D X .06 DP INSERT SCREW, ITEM #18.
- ③ WHEN REPLACING PISTON KEY, ITEM #16 OR PISTON HEAD, ITEM #9, PISTON KEY IS HELD IN PLACE BY PEENING PISTON HEAD ALONG SIDES OF PISTON KEY.

1	300685	SPRING	21
1	3-21006-8	SCREW (8-32 UNC-3A) .125 LG	20
1	23241-1	BALL	19
1	5-306105-9	SCREW (5-40 UNC-3A) .38 LG	18
1	306209-3	PIN ASS'Y	17
1	300681	PISTON KEY	16
1	23057-6	BALL PLUNGER	15
1	47510-1	HEAD SUB ASS'Y	14
2	21045-9	RING RETAINING	13
1	302312	PIN RETAINING	12
1	301555	SPACER	11
1	301556	TOPSION SPRING	10
1	48472	PISTON HEAD	9
1	3-305927-8	SCREW (10-32 UNF-3A) .56 LG	8
1	300680	PISTON RETURN SPRING	7
1	48725	PISTON	6
1	2-21107-3	WASHER	5
1	2-21053-9	"O" RING	4
1	48726	CYLINDER	3
1	1-21053-0	"O" RING	2
1	301725	CAP PLASTIC	1

DIMENSIONS IN INCHES DO NOT SCALE PRINT

REV	REVISION	DATE
R1	REVISED	12/16
R3	REVISED	8/76
R2	REVISED	8/69

REQUIRED PER ASSEMBLY		© 1968 BY AMP INCORPORATED ALL RIGHTS RESERVED AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING		CUSTOMER COPY REFERENCE ONLY	
DR P. Fitchiger 7.31.69 DC E. J. Hink 8.6.69		MATE AL AND FINISH + + +		AMP INCORPORATED HARRISBURG, PENNA.	
TOLERANCE EXCEPT AS NOTED ± .015 = 1" 0'		SCALE 1-1		CLASS + + + TYPE + + +	
NAME E. J. Hink 8.6.69		LOC M C		NO. 69065	
DESCRIPTION CRIMPING HEAD ASS'Y MOD R					