

High Value Multilayer Ceramic Capacitors (High dielectric type)

EMK021BJ102KK-W



■ Features

- Item Summary
1000pF±10%, 16V,
X5R, 008004/0201 (EIA/JIS)
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping Embossed 50000pcs

■ Products characteristics table

Capacitance	1000 pF ± 10 %
Case Size (EIA/JIS)	008004/0201
Rated Voltage	16 V
tan δ (max)	10 %
Temperature Characteristic (EIA)	X5R
Operating Temp. Range (EIA)	-55 to +85 °C
High Temperature Loading (% Rated Voltage)	150 %
Insulation Resistance (min)	10 MΩ · μF
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

■ External Dimensions

Dimension L	0.25 ± 0.013 mm
Dimension W	0.125 ± 0.013 mm
Dimension T	0.125 ± 0.013 mm
Dimension e	0.0675 ± 0.0275 mm





2017.04.29

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.

○EMK021BJ102KK

16V 0201 X5R 1000pF +/- 10% t=0.138mmMAX

16V 008004 X5R 1000pF +/- 10% t=0.0054inchMAX



部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご活用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書のご確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the data at any time without notice.

Before making final selection, please check product specification.