


DisplayPort over IP Transmitter/Receiver/Extender Kit, RS-232 Serial and IR Control, 1080p @ 60 Hz, 328 ft. (100 m), TAA

MODEL NUMBER: **B160-101-DPSI**



Converts DisplayPort™ audio/video to an IP-based signal that is transmitted point-to-point to a display 328 ft. away via Cat5e/6 cable or through a dedicated Ethernet network switch.

Description

The B160-101-DPSI DisplayPort over IP Transmitter/Receiver/Extender Kit extends and distributes DisplayPort audio/video, RS-232 serial and IR (infrared) remote signals from the source to the display located up to 328 feet (100 meters) away, which is more than 200 feet farther than a traditional Cat5e/6 solution. By adding a chain of low-cost unmanaged network switches, such as Tripp Lite's NG5, you can continue extending the distance between source and display up to 328 feet per switch.

Create a multi-in, multi-out installation with up to 64 transmitters and 255 receivers* by including dedicated managed Ethernet network switches** with Internet Group Management Protocol (IGMP), such as Tripp Lite's NSS-G16D2. You can send the DisplayPort video source to any analog or digital display, including VGA and HDMI, allowing you to mix and match technologies and use existing monitors. The IGMP-enabled switch will let you manage all connections for centralized control over which sources show on which displays.

The B160-101-DPSI supports video resolutions up to 1920 x 1080 (1080p) at 60 Hz in a point-to-multipoint switch installation. It extends IR control signals that control a source, such as a Blu-ray™ player, to a remote display, as well as RS-232 signals at serial baud rates up to 57600 Bps. The transmitter and receiver units mount to a wall, rack or pole using the including hardware.

**Unmanaged switch installations are limited to two transmitter units. Number of receivers is limited to number of ports remaining on unmanaged switch.*

Highlights

- Units connect point-to-point without a switch up to 328 ft.
- Supports video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- HDMI output on transmitter for connecting local display
- Plug and play—no software or drivers required

Package Includes

- Transmitter unit
- Receiver unit
- (2) External power supplies (Input: 100–240V, 50/60 Hz, 0.5A; Output: 5V 2A)
- Plug adapters for U.S., U.K., Europe and Australia
- IR-In cable
- IR-Out cable
- 3.5 mm to DB9 adapter cable (M/F)
- 3.5 mm to DB9 adapter cable (M/M)
- Mounting hardware
- Owner's manual



***B160-Series designed for use with dedicated network switch. Connecting to a switch used with other networking equipment will result in degraded or non-functional performance.*

Features

Extends and Distributes DisplayPort A/V, Serial and IR Control Signals over Cat5e/6 Cabling

- Converts audio/video to an IP-based signal that is transmitted point-to-point to a display 328 ft. away
- Add low-cost network switches between transmitter and receiver to continue extending distance up to 328 ft. per switch
- HDMI output on transmitter for connecting a local display

Create a Multi-In, Multi-Out Installation Using B160-Series Transmitters and Receivers

- Connect up to 64 transmitters and 255 receivers through multiple dedicated managed network switches
- IGMP-enabled switches allow centralized control over which sources show on which displays
- Video source can be sent to any analog or digital display, so you can mix and match technologies and use existing monitors

Enhanced Technical Features

- Supports video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Uses H.264 video compression standard
- Transmits on 20–60 kHz IR frequency
- Extends IR control signals that control a source from a remote display
- Supports RS-232 serial baud rates up to 57600 Bps
- HDCP and 3D compatible

Plug-and-Play Functionality

- No software or drivers required
- Hardware included for mounting on wall, rack or pole

TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

| OVERVIEW | |
|-----------------------------|--|
| UPC Code | 037332196798 |
| Technology | DisplayPort (all types); IR; Serial (RS232); A/V over IP |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 |



| | |
|---|---|
| External Power Supply Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 1.0A |
| External Power Supply Output Specs (V / A) | 5V / 2A |
| External Power Supply Cord Length (ft.) | 4.5 |
| External Power Supply Cord Length (m.) | 1.4 |
| External Power Supply DC Barrel Connector Specs | OD: 5.5 x 2.1 x 7.5mm, Positive Pin, Negative Sleeve |
| External Power Supply Plug(s) | AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America |
| External Power Supply Certifications | BSMI; CB; CE; FCC; GS; PSE; RCM; UL; cUL |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | RJ45 Output (Green / Power, Orange / Signal), Channel Signal (Red), Power (Green) |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 3.100 x 5.800 x 11.300 |
| Shipping Weight (lbs.) | 2.9000 |
| Material of Construction | SECC |
| Color | Black |
| Transmitter Unit Dimensions (hwd / in.) | 1.2 x 5 x 3.9 |
| Receiver Unit Dimensions (hwd / in.) | 1.2 x 5 x 3.9 |
| Transmitter Unit Weight (lbs.) | 0.2 |
| Receiver Unit Weight (lbs.) | 0.2 |
| Rackmountable | Yes |
| ENVIRONMENTAL | |
| Operating Temperature Range | 14 to 167 F (-10 to 75 C) |
| Storage Temperature Range | -4 to 176 F (-20 to 80 C) |
| Relative Humidity | 0% to 85%, Non-Condensing |
| BTUs | 42 BTU/Hr |
| Power Consumption (Watts) | 12.3 |
| COMMUNICATIONS | |
| Signal Range (ft.) | 328 |
| Signal Range (m) | 100 |
| Latency | 2-3 seconds |



| CONNECTIONS | |
|--------------------------------------|-------------------------------------|
| Ports | 1 |
| Side A - Connector 1 | DISPLAYPORT (FEMALE); HDMI (FEMALE) |
| Side A - Connector 2 | (2) 3.5MM (FEMALE); RJ45 (FEMALE) |
| Side B - Connector 1 | DISPLAYPORT (FEMALE) |
| Side B - Connector 2 | (2) 3.5MM (FEMALE); RJ45 (FEMALE) |
| FEATURES & SPECIFICATIONS | |
| Max Supported Video Resolution | 1920 x 1080 (1080p) @60Hz |
| Displayport Specification | 1.2 |
| HDMI Specification | 1.4 |
| HDCP Specification | 1.4 |
| Audio Specification | 2 Channel Surround Sound |
| Driver Required | No |
| Recommended Category Cable | N202-Series Cat6 Patch Cable |
| Max Supported Color Depth | 24-bit True Color |
| IR Remote Extension Support | Yes |
| RS-232 Serial Extension Support | Yes |
| 3D Video Supported | Yes |
| CERTIFICATIONS | |
| Certifications | Tested to CE, FCC, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>