


## Multilayer Chip Bead Inductors (BK Array series)

## BK20104L330-T



## ■ Features

- Item Summary  
33Ω, 0.1 A, 0804/2010 (EIA/JIS)
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping paper 4000pcs

## ■ Products characteristics table

|                               |                |
|-------------------------------|----------------|
| Impedance [100MHz]            | 33 Ω ± 25 %    |
| Case Size (EIA/JIS)           | 0804/2010      |
| Rated Current (max)           | 0.1 A          |
| DC Resistance (max)           | 0.3 Ω          |
| Z Measuring Frequency         | 100 MHz        |
| Operating Temp. Range         | -55 to +125 °C |
| RoHS2 Compliance (10 subst.)  | Yes            |
| REACH Compliance (173 subst.) | Yes            |
| Halogen Free                  | Yes            |
| Soldering                     | Reflow         |

## ■ External Dimensions

|              |                    |
|--------------|--------------------|
| Dimension L  | 2.0 ±0.15 mm       |
| Dimension W  | 1.0 ±0.15 mm       |
| Dimension T  | 0.45 ±0.05 mm      |
| Dimension E1 | 0.25 +0.15/-0.1 mm |
| Dimension E2 | 0.25 ±0.15 mm      |
| Dimension P  | 0.5 ±0.1 mm        |

2017.05.03

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.