

Test adapter - PAI-4-N GY - 3032871

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Test adapter, Color: gray



Product Features

- The small outside diameter of the test socket means that touch-proof safety plugs can also be used
- Reliable contacting of test plugs with a 4 mm diameter in the function shaft

Key commercial data

Packing unit	1 PCE
Minimum order quantity	10 PCE
Weight per Piece (excluding packing)	2.0 GRM
Custom tariff number	85366990
Country of origin	Poland

Technical data

Technical data

Color	gray
Material	PA
Inflammability class according to UL 94	V0
Minimum temperature	-40 °C
Maximum temperature	125 °C

Classifications

eCl@ss

eCl@ss 4.0	27141127
eCl@ss 4.1	27141127
eCl@ss 5.0	27141127
eCl@ss 5.1	27141111
eCl@ss 6.0	27141148

Test adapter - PAI-4-N GY - 3032871

Classifications

eCl@ss

eCl@ss 7.0	27141148
eCl@ss 8.0	27141148

ETIM

ETIM 3.0	EC000313
ETIM 4.0	EC002255
ETIM 5.0	EC002255

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411