

## Specification Sheet

Part Number: RTT750HR.NX1P



Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 25/pkg

Article Number	115-00000
Type	SpeedyTie (RTT750HR)
Color	Red (RD) Yellow (YE)
Features & Benefits	<ul style="list-style-type: none"><li>• The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.</li><li>• Additional design feature on the head allows excess strap to be tucked away after installation.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.

**Short Description**

Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 25/pkg

**Global Part Name**

SpeedyTie (RTT750HR)-PA66-RD/YE

**Minimum Tensile Strength (Imperial)**

200.0

**Minimum Tensile Strength (Metric)**

888.0

**Length L (Imperial)**

29.6

**Length L (Metric)**

752.0

**Identification Plate Position**

none

**Releasable Closure**

Yes

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.51

**Width W (Metric)**

13.0

**Bundle Diameter Min (Imperial)**

1.6

**Bundle Diameter Min (Metric)**

40.0

**Bundle Diameter Max (Imperial)**

8.3

**Bundle Diameter Max (Metric)**

210.0

**Thickness T (Imperial)**

0.075

**Thickness T (Metric)**

1.9

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Flammability**

UL 94 V2

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

25

**Package Quantity (Metric)**

25

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

23.2

