



PANEL THICKNESS	X dimension
0.75-1.25 [0.030-.049]	19.2-01 [1.756]
1.25-2.0 [0.049-.079]	19.4-01 [1.764]
2.0-3.0 [0.079-.118]	19.8-01 [1.780]



PANEL CUTOUT  
NOT TO SCALE

SWITCH FUNCTION	PDS. 1	PDS. 2
(DN)	DN	DN
1-1a	1-1a	1-1a



( ) = MOMENTARY

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. RATING: 15A @ 125VAC OR  
8A @ 250VAC
5. MATERIALS: TERMINALS: Silver Plated Copper Alloy  
CONTACTS: Coin Silver, Silver Plated
6. ELECTRIC LIFE: 10,000 cycles
7. CONTACT RESISTANCE: <20 Mega Ω
8. INSULATION RESISTANCE: >1000 Mega Ω
9. DIELECTRIC STRENGTH: >1500 V 1 minute  
>3000 V between poles
10. 2002/95/EC (ROHS) COMPLIANT



REV.	ECN NO.	DESCRIPTION	DATE	CHKD
A	17154	RELEASED FOR PRODUCTION	4/4/07	TN
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED				

TITLE	SCALE	DATE	DR	DWG	REV
R1966FBLKREDEF	1.5:1	4/4/2007	TN	M305203	A