

## Half screw connection - VC-M-KV-PG16(11,5-15,5) - 1854857


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Half screw connection Pg16, made of metal, consisting of rubber seal with one hole and one pressure screw, for type 1 housings, cable [mm] 11.5 - 15.5

RoHS

### Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 5 STK   |
| GTIN         | <br>4 017918 146047 |
| GTIN         | 4017918146047   |

### Technical data

#### Dimensions

|                         |                     |
|-------------------------|---------------------|
| Wrench size, union nut  | 24 mm               |
| External cable diameter | 11.5 mm ... 15.5 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Degree of protection            | IP67              |
| Ambient temperature (operation) | -40 °C ... 125 °C |

#### General

|                              |  |
|------------------------------|--|
| Note                         | Adapter screw connections are available on request for large cable dimensions, from Pg16 to Pg21 and from Pg21 to Pg29 |
| No. of conductors            | 1  |
| Material, pressure screw     | Nickel-plated brass  |
| Seal material                | TPE  |
| Cable seal material          | TPE  |
| Shielded                     | no   |
| Thread type on seal side     | Pg16   |
| Tightening torque, union nut | 7.50 Nm  |

#### Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

# Half screw connection - VC-M-KV-PG16(11,5-15,5) - 1854857

## Technical data

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

---

Approvals


EAC

---

Ex Approvals

---

### Approval details

|     |   |         |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>