
TECHNICAL DATA
DATA SHEET D0042 REV. A

SILICON ZENER DIE

Features:

- Zener Voltage 3.3V - 47V
- Withstand Large Surge Stresses

Maximum Ratings:

Characteristics	Symbol	Condition	Max.	Units
Nominal Power Dissipation	P_D	Derate above 25 °C	3	W
Forward Voltage	V_F	@ $I_F=200\text{mA}$, Pulse, $T_J = 25\text{ °C}$	1.1	V
Maximum DC Zener Current	I_{ZM}	-	55	mA
Operating Temperature Range	T_J	-	-40 to +165	°C
Storage Temperature Range	T_{stg}	-	-65 to +150	°C

**TECHNICAL DATA
DATA SHEET D0042 REV. A**


Electrical Characteristics @ T_J =25 °C:

Device	Zener voltage		Zener Impedance			Leakage Current	
	Nom. VZ ①	@ I _{ZT}	Max.	Max.	@ I _{ZK}	Max. I _R @ V _R	
			Z _{KT} @ I _{ZT}	Z _{KK} @ I _{ZK}			
	Volts	mA	Ω	Ω	mA	uA	Volts
SZ373V3	3.3	113.6	10	500	1	100	1
SZ373V6	3.6	104.2	9	500	1	75	1
SZ373V9	3.9	96.1	7.5	500	1	25	1
SZ374V3	4.3	87.2	6	500	1	5	1
SZ374V7	4.7	79.8	5	500	1	5	1.5
SZ375V1	5.1	73.5	4	350	1	5	2
SZ375V6	5.6	66.9	2	250	1	5	3
SZ376V2	6.2	60.5	2	200	1	5	4
SZ376V8	6.8	55.1	2.5	200	1	5	5.2
SZ377V5	7.5	50	3	400	0.5	5	6
SZ378V2	8.2	45.7	3.5	400	0.5	5	6.5
SZ379V1	9.1	41.2	4	500	0.5	5	7
SZ3710	10	37.5	4.5	500	0.25	5	8
SZ3711	11	34.1	5.5	550	0.25	1	8.4
SZ3712	12	31.2	6.5	550	0.25	1	9.1
SZ3713	13	28.8	7	550	0.25	1	9.9
SZ3714	14	26.7	8	600	0.25	1	10.5
SZ3715	15	25	9	600	0.25	1	11.4
SZ3716	16	23.4	10	650	0.25	1	12.2
SZ3717	17	22	11	650	0.25	1	13
SZ3718	18	20.8	12	650	0.25	1	13.7
SZ3719	19	19.7	13	650	0.25	1	14.4
SZ3720	20	18.7	14	650	0.25	1	15.2
SZ3722	22	17	17.5	650	0.25	1	16.7
SZ3724	24	15.6	19	700	0.25	1	18.2
SZ3725	25	14.9	20	700	0.25	1	19.2
SZ3727	27	13.9	23	700	0.25	1	20.6
SZ3728	28	13.4	24	750	0.25	1	21.4
SZ3730	30	12.5	26	750	0.25	1	22.8
SZ3733	33	11.4	33	800	0.25	1	25.1
SZ3736	36	10.4	38	850	0.25	1	27.4
SZ3739	39	9.6	45	900	0.25	1	29.7
SZ3743	43	8.7	53	950	0.25	1	32.7
SZ3747	47	8	67	1000	0.25	1	35.8


Note: ①Vz Tolerance is ±5%

**TECHNICAL DATA
DATA SHEET D0042 REV. A**

Mechanical Dimensions: In mil (mm)



Bottom side metalization Ag-5kA minimum
 Top side metalization AlSiCu -25kA minimum
 Bottom side is cathode, top side is anode
 Dimension H = $8.2 \pm 1(0.21 \pm 0.025)$ (It can be customized according to customer requirements)



A	B
$37 \pm 2(0.94 \pm 0.05)$	$30 \pm 2(0.76 \pm 0.05)$

DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC - Sangdest Microelectronics (Nanjing) Co., Ltd sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC - Sangdest Microelectronics (Nanjing) Co., Ltd assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..