

## Specification Sheet

Part Number: T120R0HSK2



High-Temp Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, PA66HS, Black, 50/pkg

Article Number	111-12061
Type	T120R
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Heat stabilized heavy duty cable ties provide excellent resistance to high heat exposures.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

High-Temp Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, PA66HS, Black, 50/pkg

**Global Part Name**

T120R-PA66HS-BK

**Minimum Tensile Strength (Imperial)**

120

**Minimum Tensile Strength (Metric)**

535

**Length L (Imperial)**

15.2

**Length L (Metric)**

387.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.30

**Width W (Metric)**

7.6

**Bundle Diameter Min (Imperial)**

0.20

**Bundle Diameter Min (Metric)**

5.0

**Bundle Diameter Max (Imperial)**

4.1

**Bundle Diameter Max (Metric)**

104.1

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
-----------------	--

<b>Material Shortcut</b>	PA66HS
--------------------------	--------

<b>US MIL SPEC</b>	MIL 53421	<b>Flammability</b>
--------------------	-----------	---------------------

UL 94 V2	<b>Halogen free</b>
----------	---------------------

Yes	<b>Operating Temperature (Metric)</b>
-----	---------------------------------------

-40°F to +257°F (-40°C to +125°C)	<b>ROHS Complaint</b>
-----------------------------------	-----------------------

Yes	<b>Certification/Specification WEB</b>
-----	--

VG U48/04103 UL-ZODZ2.E64139	<b>UL Recognized (US)</b>
------------------------------	---------------------------

Yes	<b>UL Listed (US and Canada)</b>
-----	----------------------------------

Yes	<b>UL Recognized (US and Canada)</b>
-----	--------------------------------------

Yes

<b>Package Quantity(Imperial)</b>	50
-----------------------------------	----

<b>Package Quantity (Metric)</b>	50
----------------------------------	----

<b>Customs Number</b>	3926909987
-----------------------	------------

