THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

PART NUMBER	REV	TERMINATOR	FEED TYPE	DESCRIPTION
1528770-1	A	LEADMAKER	MECH POST FEED	CUTS CARRIER
1528770-2	A	BENCH	MECH PRE FEED	CUTS CARRIER
1528770-6	A	LEADMAKER	MECH POST FEED	CONTINUOUS CARRIER
7-1528770-1	A	LEADMAKER	MECH POST FEED	-1 AND SPARE PARTS
7-1528770-2	A	BENCH	MECH PRE FEED	-2 AND SPARE PARTS
7-1528770-6	A	LEADMAKER	MECH POST FEED	-6 AND SPARE PARTS
7-1528770-7	A	-	-	SPARE PARTS KIT

CRIMP DATA TYCO TERMINAL TYCO CRIMP SPECS			
TERMINAL NAME: DIA 4mm SOCKET CONTACT			
CRIMP	SIZE	TYPE	RANGE
WIRE	3.05 [.120 IN]	F	>2.50mm²-4.00mm²
INSUL	3.94 [.155 IN]	O	2.70-3.70 [.106-.146 IN] △5
WIRE STRIP LENGTH 4.70-5.30 [.185-.209 IN]			APPL INSTRUCTIONS 408-8322 & 408-8490
TERMINAL APPL SPEC	114-18022 - -		FEED 19.80 [.780 IN]

TERMINALS APPLIED

1703420	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

WIRE SIZE	CRIMP HEIGHT *	REF SETTING *
4.00mm²	2.30 ±0.05 [.091 ±.002 IN]	B6
3.00mm²	2.05 ±0.05 [.081 ±.002 IN]	D5
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

△1 RECOMMENDED SPARE PARTS.

2. GREASE RAM, CAM, CAM FOLLOWER AND FEED ROD LIGHTLY.

△3 CERTAIN TERMINALS REQUIRE LUBRICATION. REFER TO THE APPLICATOR INSTRUCTION SHEET FOR MORE INFORMATION.

4. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

△5 TERMINAL APPLIES FLR TYPE INSULATION.

△6 ITEM 53, CUT TO LENGTH AT ASSEMBLY.

* WARNING
ON INSTALLATION, SET WIRE DISC TO LARGEST WIRE SIZE SETTING. USE OF SETTINGS BELOW MIN. REQUIRED CRIMP HEIGHT SETTING WILL CAUSE DAMAGE TO CRIMP TOOLING.





FEED TRACK POSITION GUIDE BY WIRE BARREL



TERMINAL SUPPORT LOCATION



VIEW B ROTATED 180°



ITEM NO	DESCRIPTION	PART NO	-1	-2	-6	-71	-72	-76	-77
84	-	-	-	-	-	-	-	-	-
83	-	-	-	-	-	-	-	-	-
82	-	-	-	-	-	-	-	-	-
81	-	-	-	-	-	-	-	-	-
80	-	-	-	-	-	-	-	-	-
79	-	-	-	-	-	-	-	-	-
78	-	-	-	-	-	-	-	-	-
77	-	-	-	-	-	-	-	-	-
76	-	-	-	-	-	-	-	-	-
75	-	-	-	-	-	-	-	-	-
74	-	-	-	-	-	-	-	-	-
ITEM NO	DESCRIPTION	PART NO	-1	-2	-6	-71	-72	-76	-77

SET UP GAGE 458637-3

LOC	DIST
A	66

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	SEE ECO-07-016199	11JUL2007	DP	MC

ITEM NO	DESCRIPTION	PART NO	-1	-2	-6	-71	-72	-76	-77
73	-	-	-	-	-	-	-	-	-
72	-	-	-	-	-	-	-	-	-
71	DOCUMENTATION PACKAGE	1338705-3	1	1	1	1	1	1	-
70	-	-	-	-	-	-	-	-	-
69	-	-	-	-	-	-	-	-	-
68	-	-	-	-	-	-	-	-	-
67	PLATE, IDENTIFICATION	461264-5	1	1	1	1	1	1	-
66	SCREW, DRIVE	21017-2	2	2	2	2	2	2	-
65	-	-	-	-	-	-	-	-	-
64	-	-	-	-	-	-	-	-	-
63	SCR, SET, CUP POINT M6 X 6.0	3-18031-0	1	1	1	1	1	1	-
62	-	-	-	-	-	-	-	-	-
61	SCR, SET, FLT POINT M5 X 20.0	2-18032-5	2	2	2	2	2	2	-
60	SCR, BTN SKT HD CAP (M4 X 10.0)	18024-7	1	1	1	1	1	1	-
59	SCR, HEX HD CAP M4 X 8.0	5-18022-2	1	1	1	1	1	1	-
58	-	-	-	-	-	-	-	-	-
57	-	-	-	-	-	-	-	-	-
56	PAWL, FEED	1338685-1	1	1	1	1	1	1	-
55	-	-	-	-	-	-	-	-	-
54	SCR, BTN SKT HD CAP (M4 X 12.0)	18024-8	4	4	4	4	4	4	-
53 △6	SCR, SKT HD CAP M4 X 16.0	1-18023-3	2	2	2	2	2	2	-
52	NUT, HEX, REG M3	18030-1	1	1	1	1	1	1	-
51	BUMPER, HOLD DOWN	811242-5	1	1	1	1	1	1	-
50	SPACER, TONKER	690753-2	1	1	1	1	1	1	-
49	SCR, BTN SKT HD CAP (M3 X 10.0)	18024-3	1	1	1	1	1	1	-
48	CAM, UNIVERSAL PRE FEED	1338675-1	1	-	-	1	-	1	-
47	CAM, UNIVERSAL POST-FEED	1338676-1	1	-	1	1	-	1	-
46	APPLICATOR SUBASSEMBLY, HDI	1320999-3	1	1	1	1	1	1	-
45	PLUG,NYLON	690191-1	1	1	1	1	1	1	-
44	RAM	1333257-1	1	1	1	1	1	1	-
43	-	-	-	-	-	-	-	-	-
42	-	-	-	-	-	-	-	-	-
41	SCR, BTN SKT HD CAP (M8 X 25.0)	2-18024-6	1	1	1	1	1	1	-
40	-	-	-	-	-	-	-	-	-
39	SHIM SUB-ASSY	690125-1	1	1	1	1	1	1	-
38	SHIM	1-469367-0	1	1	1	1	1	1	-
37	FINE ADJUST HEAD ASSEMBLY	879103-2	1	1	1	1	1	1	-
36	-	-	-	-	-	-	-	-	-
35	-	-	-	-	-	-	-	-	-
34	SUPPORT, TERMINAL	1-1320934-3	1	1	1	1	1	1	-
33	SCR, BTN SKT HD CAP (M4 X 20.0)	1-18024-0	2	2	2	2	2	2	-
32	WASHER, FLAT, REG M4	18027-2	1	1	1	1	1	1	-
31	SCR, SKT HD CAP M4 X 12.0	1-18023-2	1	1	1	1	1	1	-
30	SPACER, STRIP GUIDE	1320908-2	1	1	1	1	1	1	-
29	STRIP GUIDE ASSEMBLY	1633073-2	1	1	1	1	1	1	-
28	SPACER, CRIMPER	1-455888-0	1	1	1	1	1	1	-
27	SPRING, COMPRESSION	1-22284-0	2	2	2	2	2	2	-
26	LEVER, DRAG RELEASE	356835-1	1	1	1	1	1	1	-
25	DRAG, TERMINAL	240792-1	1	1	1	1	1	1	-
24	PLATE, STRIP GUIDE	1320928-1	1	1	1	1	1	1	-
23	SCR, SKT HD SHLDR 5.0 DIA X 6.0	980371-4	1	1	1	1	1	1	-
22	STRIPPER	690472-2	1	-	1	1	-	1	-
21	SCR, SKT HD CAP M4 X 10.0	1-18023-1	1	1	1	1	1	1	-
20	WASHER, SPRG LOCK, REG M4	18025-2	4	4	4	4	4	4	-
19	STRIPPER	690472-1	1	-	1	-	-	-	-
18	-	-	-	-	-	-	-	-	-
17 △1	SHEAR HOLDER, FRONT	1338684-1	1	-	1	-	-	-	-
16	-	-	-	-	-	-	-	-	-
15	-	-	-	-	-	-	-	-	-
14	-	-	-	-	-	-	-	-	-
13	-	-	-	-	-	-	-	-	-
12	SPRING, COMPRESSION	3-22280-3	1	1	1	1	1	1	-
11	STOP, SHEAR	356885-4	1	1	1	1	1	1	-
10 △1	SHEAR HOLDER, FRONT, CUT	1320921-1	1	-	1	-	-	-	-
9 △1	FLOATING SHEAR, FRONT	454276-1	1	1	1	1	1	1	-
8 △1	ANVIL, COMBINATION .120	1633135-5	1	2	2	2	2	1	-
7	SPACER	240641-5	1	1	1	1	1	1	-
6	-	-	-	-	-	-	-	-	-
5	DEPRESSOR, SHEAR	3-455889-6	1	1	1	1	1	1	-
4	BLOCK, CRIMPER SPACER	238011-2	1	1	1	1	1	1	-
3 △1	CRIMPER, INSULATION O PREMIUM	1-456135-0	1	2	2	2	2	1	-
2	SPACER, CRIMPER	1-455888-1	1	1	1	1	1	1	-
1 △1	CRIMPER, WIRE .120 "F" PREMIUM	456409-3	1	2	2	2	1	1	-
ITEM NO	DESCRIPTION	PART NO	-1	-2	-6	-71	-72	-76	-77

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

DWN 01MAR2007 D PROUSE
CHK -
APVD 01MAR2007 M.CLIFFORD
PRODUCT SPEC -
APPLICATION SPEC See Table
WEIGHT -
DIMENSIONS: mm [IN]
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-
MATERIAL - -
FINISH - -

tyco Electronics
Tyco Electronics
Harrisburg, PA 17105-3608

NAME FINE ADJUST SIDE FEED HDI APPLICATOR -

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-1528770	-

CUSTOMER DRAWING SCALE 3:5 SHEET 1 OF 1 REV A