



IMPEDANCE (Z)			
Frequency	25 MHz	100 MHz	300 MHz
Nominal (REF)	46 Ω	129 Ω	312 Ω
Minimum	- Ω	103 Ω	- Ω




AGILENT E4991A Impedance/Material Analyzer
HP 16092A Test Fixture, REF # 2801

FERRITE CORE DIMENSIONS (SPEC):mm[Inches]


A	32.00 [1.260]	+ 0.50 [.020]
B	27.80 [1.094]	+ 0.50 [.020]
C	14.66 [.577]	+ 0.40 [.016]
D	7.75 [.305]	+ 0.50 [.020]
E	1.30 [.051]	Min.

WEIGHT/1000 13.88 kgs [30.60 Lbs]



DETAIL A
SCALE 6:1

UNCONTROLLED DOCUMENT



DIMENSIONS ARE IN mm[INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.		
PROJECT/PART NUMBER:				REV	PART TYPE:	DRAWN BY:
28R1259-400				A	FERRITE RIBBON CORE	Jcai
DATE:			SCALE:	MATERIAL:		
06/05/12			2 : 1	FERRITE		
REV	DESCRIPTION	DATE	INT	CAD #	TOOL #	
A	ORIGINAL DRAFT	06/05/12	Jcai	28R1259-400-A	R1259	

