



HEAVY  
DUTY

- 13,500 Cycles\*
- 20 Mil Wall Thickness
- 1,000 Denier Cordura, Double Coated with Proprietary High FR Neoprene
- Extreme, Oversized Hook & Loop Closure
- Repels Liquids
- Prevents Damage From UV, Abrasion, And Salt Water
- Resists & Sheds Sparks And Hot Spall
- Non-Wicking

## Protection Sleeve With Easy On, Easy Off Hook And Loop Closure

TURTLE WRAP (DWT) is made of 1,000 Denier Cordura® and double coated with proprietary high FR Neoprene. This protection sleeve is used for bundling and wrapping hoses and cables. The reusable sleeve features Mil-Spec extreme Hook & Loop closure, which allows installation without disconnecting hoses and can reduce labor time by 70%.

DWT is an excellent choice for weld cable or welding hose that is often dragged across the floor. This material resists sparks and hot spall. Turtle Wrap is also used in subsea maintenance where barnacles, sea life, and salt water can damage hoses. This sleeve is also heavily used on off-shore oil rigs.



With built in flame retardancy, your imagination is the limit for things you can protect.



Nominal Size	Part #	Wall Thickness	Hook & Loop Width	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1"	DWT1.00BK	.02"	1 1/4"	150'	25'	Black (BK)	6.00
1 1/2"	DWT1.50BK	.02"	1 1/4"	150'	25'	Black (BK)	7.20
1 3/4"	DWT1.75BK	.02"	1 1/4"	150'	25'	Black (BK)	9.29
2"	DWT2.00BK	.02"	1 1/4"	150'	25'	Black (BK)	10.41
2 3/8"	DWT2.38BK	.02"	1 1/4"	150'	25'	Black (BK)	11.10
2 1/2"	DWT2.50BK	.02"	1 1/4"	150'	25'	Black (BK)	11.60
3"	DWT3.00BK	.02"	1 1/4"	150'	25'	Black (BK)	13.80
3 1/2"	DWT3.50BK	.02"	1 1/4"	150'	25'	Black (BK)	15.33
4"	DWT4.00BK	.02"	1 1/4"	150'	25'	Black (BK)	16.80
6"	DWT6.00BK	.02"	1 1/4"	150'	25'	Black (BK)	22.00

CORDURA® is a registered trademark of INVISTA.

Abrasion Resistance

630	950	2,500	3,500	4,400	8,500	13,000+
-----	-----	-------	-------	-------	-------	---------

HIGH

EXTREMELY HIGH

1-973-300-9242  
www.techflex.com

